



PRECISION, QUALITY & INNOVATION

DF by Moyer Diebel Glasswasher

- ▲ Fast cleaning cycle is ideal for high volume locations.
- ▲ Cool final rinse cycle provides ready-to-use glassware.
- ▲ Polypropylene conveyor helps prevent damage to stemware.

Leasing a dishmachine from Ecolab allows you to focus on your business with the security of knowing your warewashing operation is properly managed.



# Superior Results, 24/7 Service and a Great Financial Option.

## SPECIFICATIONS

OPERATING TEMPERATURES	
Wash (minimum)	120° F
Sanitizing Rinse (minimum)	75° F
WATER CONSUMPTION	
Gallons per Minute (cold water)	2.8
ELECTRICAL RATINGS	
Wash Pump	1/10 hp
WEIGHT	
Machine Weight	154 lbs
UTILITY REQUIREMENTS ELECTRICAL	
Voltage/Frequency/Phase:	
208-240V/60Hz/1 Ph	
Total Amperage	13A
Minimum Electrical Circuit	20A
WATER	
Waterline Size (min)	1/2"
Flow Pressure (required)	25-95 psi
Minimum Incoming Temperature	140-160°F
DRAIN	
Drainline Size (min)	1-1/2"
CHEMICAL SANITIZER RINSE	
Minimum chlorine, ppm	50
Minimum iodophor, ppm	12.5

- 1 Hot Water Connection:**  
 140-160°F/60-71°C  
 ½" IPS  
 Flow pressure 25-95 PSI [173-655 kPa].

Install water shut-off valves and check-valves in the water inlet supply lines and as close to the machine as possible.
- 2 Cold Water Connection:**  
 75°F/24°C  
 ½" IPS  
 Flow pressure 25-95 PSI [173-655 kPa].

Install water shut-off valves and check-valves in the water inlet supply lines and as close to the machine as possible.
- 3 Drain Connection:**  
 Gravity  
 1½" Tailpiece (slip-fit)  
 Maximum drain flow 3 US gallons/min [11L/min]
- 4 Electric Connection:**  
 208-230VAC/50-60HZ/1PH  
 Min/Max 15A  
 6 ft. /1.5 m flexible cord and plug supplied  
 NEMA 6-15P electric outlet

